



Fresh Refrigeration
www.Grandmfg.net

Project Name: _____

SIA #

Location: _____

Item #: _____ Qty: _____

AIA #

Model #: _____

Model:
GSR-72-HC

Fresh Reach-In Series
3 door bottom mount refrigerator



Features & Benefits

Cabinet Construction

- Stainless steel interior, and exterior; quality stainless steel helps to minimize dents, scratches, and rust.
- Entire cabinet structure and solid door are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Sturdy, epoxy coated wire shelves with adjustable shelving height.
- Designed to accommodate full-size roll-in racks for bun sheet pan (18"L x 26"D)

Refrigeration

- Hydrocarbon refrigerants (R-290): Innovative eco-friendly technology, R290 hydrocarbon refrigerant has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Anti-corrosion epoxy coated evaporator helpsto eliminate the potential corrosion.
- Automatic defrost and fabric condensate evaporation system.
- Refrigerators hold 32°F ~ 39°F and freezers hold -10°F~0°F

Doors

- Self-closing Doors
- Durable door gasket with easy replacement, Self-adjusting magnetic gaskets.
- Heavy-duty Insulation thickness.
- Pressure relievers are equipped to eliminate vacuum pressure and allows doors to easily open
- Standard door lock system

Design & Features

- Digital temperature control & monitor system; keep food products safe by maintaining constant temperatures, digital display allows for easy monitoring, includes a self-diagnosis program that automatically helps interpret the condition of the refrigeration system.

Lighting

- LED Interior lighting

Standard

- NSF/ANSI Standard 7

Doors	Shelves	HP	AMPS	Cabinet Dimensions (inches)			Crated Weight (lbs.)
				W	D	H	
3	9	3/8	9.5	82 1/4	31 1/8	78 1/2	551

* External dimensions do not include 4" caster height.

** FRESH has the right to change specifications without further notice.



Approvals:

Available At:


Model:
GSR-72-HC

Fresh Reach-In Series


3 door bottom mount refrigerator

Plan View

Front View



Top View



Spec

Electrical Data	
Voltage	115/60/1
Plug Type	NEMA 5-15P
Full load Amperes	9.5
Compressor HP	3/8
Refrigerant	R-290

Dimensional Data	
#of Rackks Accepted	3
Capacity (cu. ft.)	67.5
Net Weight (lbs.)	485
Shelf Size (L x D) (in.)	23.62 x 23.78 (Left/Right)
	26.38 x 23.78 (Middle)

Warranty

- 3 years labor warranty.
- 5 years parts warranty
- 10 years compressor warranty

Optional Accessories

- Additional PE coated wire shelf (Sides)
- Additional PE coated wire shelf (Middle)

Slight Variations May Exist

Fresh

Fresh Refrigeration
www.Grandmfg.net

